

A B B D Additional stops include 10' of height for each stop 2-Stop overall height up to 20' included. Overall Height Floor to Floor Height Loading

1 HP, (208 V, 230 V, or 460 V), 60Hz single or 3 phase motor UL classified elevator controller

> Powder coated car, rail assembly, and trolley Call / Send stations

Elevator interlocks (Hoistway doors are not included)

Safety switch for motor access panel/door

Adjustable limits Top and bottom final limits

Custom car size at no charge up to a maximum of 30" x 30" x 36" or 18.75 cu.ft. Max.

Car can be open on any 3 sides at no charge.


Motor can be on the bottom or on top. (Specify bottom or top motor mount when ordering) Pillow block assembly opposite motor


Size 40 roller chain (3,125 lb breaking strength)


Additional Options

Extra stops Fixed or adjustable shelves Powder coated car panels Stainless steel car Car gates Bi-parting car gates

Car here lights Keyed On/Off switch Elevator interlocks ASME A17.1 package Hoistway doors 1 HP, 230 V, 50Hz, 3 phase motor for European market







Dumbwaiter Sales

500 Cathedral Dr. Aptos, CA 95001 831-999-3399 / Fax: 831-476-7314 / Gil@DumbwaiterSales.com THE SMART WAY TO BUY A DUMBWAITER ~